


Model GL

G-Link™ Coupler

 In-Stock

Product Features:

- Forged steel (unless noted)
- Can be used to make a Quick-Choke™ Pipe Lifting Sling
- Couples web or round sling with hardware (oblongs or hooks)
- Splices two slings into longer length
- Connects two slings with oblong and two hooks into bridle sling
- Plated for corrosion resistance
- Complies with ASME B30.9 sling capacities



Patent No. 5,651,573

WARNING

Load loss. G-Link is not a hook.
Do not use the G-Link as a hook. Use G-Link only for connecting slings or end fittings.


G-Link™ Hardware

| Model Number | Rated Capacity (tons) | Dimensions (inches) | | | | | | Weight (lbs.) |
|--------------|-----------------------|---------------------|---------|----------|-------------|-----------|----------|---------------|
| | | Sling Size | Width W | Length H | Thickness T | Opening O | Radius R | |
| GL2 | 2-1/2 | 2 | 3-5/8 | 5 | 1/2 | 1/2 | 1/2 | 2.2 |
| GL3 | 5 | 3 | 5 | 6-5/8 | 3/4 | 9/16 | 5/8 | 5.6 |
| GL4 | 7-1/2 | 4 | 6 | 7-1/2 | 1 | 3/4 | 11/16 | 9.5 |
| GL5* | 15 | 5 | 8 | 10 | 1-1/4 | 9/16 | 1 | 22.7 |
| GL6* | 25 | 6 | 9-1/2 | 12-1/2 | 1-1/2 | 1-3/16 | 1 | 37 |

* Flame cut steel

In Stock - Items with green model numbers ship in 48 hours, excluding weekends and holidays.

MODELGL



Use to make these Quick-Choke™ Slings:

| Model Number | Rated Capacity (lbs.) | Web Sling | |
|--------------|-----------------------|-------------|--------------|
| | | Width (in.) | Length (ft.) |
| QC-2 | 4000 | 2 | 10 |
| QC-3 | 7000 | 3 | 12 |
| QC-4 | 9000 | 4 | 14 |

In Stock - Items with green model numbers ship in 48 hours, excluding weekends and holidays.

PRODUCT OPERATION



Quick-Choke™ Sling.



Connect Hook Or Oblong To Sling.



Connect Two Slings (Configuration will affect G-Link™ capacity.)

Model PSB

Web Sling Quick Disconnects

 In-Stock

Product Features:

- Flame-cut steel
- Quick and easy choker with rigging
- Sized for 2" and 3" wide slings
- Ideal for handling pipe quickly and efficiently
- Plated for corrosion resistance.
- 5' minimum length
- Complies with ASME B30.9 sling capacities



PRODUCT OPERATION



Use to make these Quick Disconnect Slings in any length your customer needs!

| Model Number | Rated Capacity (lbs.) | Web Sling Width (in.) |
|--------------|-----------------------|-----------------------|
| D2PS-Q | 2500 | 2 |
| D3PS-Q | 3750 | 3 |

Quick Disconnect Hardware

| Model Number | Rated Capacity (lbs.) | Webbing Slot | | Overall Length (in.) | Weight of Unit (lbs.) |
|--------------|-----------------------|--------------|--------------|----------------------|-----------------------|
| | | Width (in.) | Length (in.) | | |
| PSB-2 | 2500 | 2-1/8 | 7/8 | 3-3/8 | 2 |
| PSB-3 | 3750 | 3-1/4 | 1 | 3-5/8 | 5 |

NOTE: Both pieces sold as a unit.

In Stock - Items with green model numbers ship in 48 hours, excluding weekends and holidays.