

Synthetic Sling End Fittings

Aluminum Triangles and Chokers



Triangles


PRODUCT FEATURES:

- Forged aluminum.
- Lightweight for one-ply capacity slings only.
- Non-sparking.
- Complies with ASME B30.9 sling capacities.



Chokers


INSTOCK PROGRAM



SPECIFICATIONS - Triangles

Model Number	Rated Capacity (lbs.)	Dimensions (in.)			Weight (lbs.)
		A	B	Thickness	
AT2	3360	3/4	2-1/4	9/16	.32
AT3	5000	3/4	3-1/4	5/8	.70
AT4	6700	7/8	3-3/4	1/2	1.2
AT6	9700	1-1/16	5-1/2	15/16	2.75

NOTE: For use only with one-ply web slings.



SPECIFICATIONS - Chokers

Model Number	Rated Capacity (lbs.)	Dimensions (in.)			Weight (lbs.)
		A	C	Thickness	
AC2	3360	3/4	4-1/4	9/16	.72
AC3	5000	3/4	5-1/4	11/16	1.2
AC4	6700	7/8	6-3/4	1/2	1.8
AC6	9700	1-1/16	8-1/2	15/16	4.9

NOTE: For use only with one-ply web slings.

WARNING

Do not use aluminum fittings where fumes, sprays, mists or liquids of caustics are present.